

## Adhesives & Sealants for Lighting

Permabond Engineering Adhesives manufactures adhesives that are trusted for the many bonding, coating and sealing applications found in lighting manufacturing and assembly.

**Lighting manufacturers serving the following industries have unique adhesive requirements.**

- Architectural Lighting
- Commercial Lighting
- Consumer Lighting
- Industrial Lighting
- LED Lighting
- Optical Lighting
- Parking Lot Lighting
- Residential Lighting
- Roadway Lighting
- Safety Lighting
- Stadium Lighting
- Theater Lighting
- Vehicle Lighting

**Permabonds diverse adhesive technologies provide manufacturing solutions for all lighting industries.**



**Ideal for bonding:**

ABS

Acrylic

Aluminium

Carbon Fibre

Composite

EPDM

Ferrite

FRP & GRP

Glass

Laminate

Leather

Nylon

Phenolic

Polycarbonate

Polyethylene\*

Polypropylene\*

Polystyrene

PVC

Rubber

Steel

Titanium

Zinc

+Many more materials  
\*Specific grades only

# Permabond Adhesives for Lighting

Application Description	Grade	Type	Features	Temperature Resistance	Handling Time
Dome Coating	UV683	UV Cure	Fast, tack free, clear, non-yellowing protective coating	-55 to +120°C -65 to +248°F	3.5 sec @ 33mW/cm2
Potting	ET500	2-part Epoxy	Fast, clear, low viscosity and non-yellowing	-40 to +80°C -40 to +175°F	5 - 8 min
Thermal Management	ES578	1-part Epoxy Heat Cure	Electrically insulating, thermal conductivity 1.5W/(m.K)	-40 to +180°C -40 to +355°F	30 min @ 150°C (300°F) (full cure)
Thermal Management	TA4392	Surface Activated - use with Initiator 41	Structural Acrylic Thermal Conductivity 1.1W/(m.K)	-55 to +165°C -65 to +329°F	10-30 sec
Thermal Management	MT3286	2- part Modified Epoxy	Soft and flexible. Thermal Conductivity 1.5W/(m.K)	-40 to +120°C -40 to +250°F	2 - 3 hours
Wire Tacking	947, CSA NF	Instant Adhesive Accelerator	Fast strong bonds to a variety of surfaces.	-55 to +80°C -65 to +180°F	10 sec
LED Strip Bonding	ET515	2-part Epoxy Room Temp Cure	Dual cartridge with static mix nozzles bond flexible LED strips	-40 to +80°C -40 to +175°F	25 min
	MS359 Clear	MS Polymer	One part moisture cure, excellent weather resistance	-40 to +100°C -40 to +212°F	20 min (skin over time)
Reflector Bonding	820	Instant Adhesive Room Temp Cure	Single component, high temperature resistant	-55 to +200°C -65 to +392°F	10 sec
Reflectors / Housing Bonding	920	Instant Adhesive Room Temp + Heat Cure	Highest temperature resistant instant adhesive	-55 to +250°C -65 to +482°F	10 sec
LED Enclosures / On/Off Buttons	940 series	Instant Adhesives Room Temp Cure	Low odor, Non-blooming grades range from 7cPs to 1200cPs	-55 to +80°C -65 to +180°F	10 sec
PC Lens Bonding	UV630	UV Cure	UV630 is ideal for bonding polycarbonate lenses	-55 to +120°C -65 to +248°F	<5 sec @ 33mW/cm2 (full cure)
Glass Lens Bonding	UV6160	UV Cure	UV6160 forms crystal clear glass to metal bonds	-55 to +120°C -65 to +248°F	<2 sec LED
Underwater Lens Bonding	UV6231	UV Cure	UV6231 forms bonds which withstand exposure to water	-55 to +120°C -65 to +248°F	<2 sec LED
Threadlocker	A113* MM115**	Anaerobic	Seals and locks fasteners against vibration loosening	-55 to +150°C -65 to +300°F	10-15 min
Glass Lens Bonding	UV612T	UV and Heat Cure	Crystal clear bonds which resist yellow / high refractive index.	-55 to +120°C -65 to +248°F	<20 sec low power

\*Available in Europe, Middle East & Australia

\*\*Available in The Americas & Asia

For full, up-to-date technical information, please refer to the TDS (Technical Data Sheet).

**Above is only a small sampling of products. If you don't see the exact product you are looking for, or need more in depth technical information, Permabond's technical team would be more than happy to help. Contact us at [info.americas@permabond.com](mailto:info.americas@permabond.com) or 800- 714- 0170.**

[www.permabond.com](http://www.permabond.com)

- **US Helpline - 800-640-7599**
- **UK - 0800 975 9800**
- **Asia + 86 21 5773 4913**
- **General Enquiries +44(0)1962 711661**
- **Deutschland 0800 101 3177**
- **France 0805 111 388**

[info.europe@permabond.com](mailto:info.europe@permabond.com)

[info.americas@permabond.com](mailto:info.americas@permabond.com)

[info.asia@permabond.com](mailto:info.asia@permabond.com)



Distributor Stamp